

SUPER THERM




R20 EQUIVALENT INSULATION COATING

- 70% of Japan Marketshare
- NASA Technology 2000 participant
- Resists Fire & Chemicals
- Blocks 99.5% infrared heat
- Spray - Roll - Brush
- Interior or Exterior Application



SUPER THERM MultiCeramics© technology provides corrosion protection and "plating" that reduces surfaces maintenance for 3 to 4 times the normal life span of any application, it saves energy, provides longer life to properties and surfaces. Unlike the alternative fiberglass or foams, it poses no health hazards and offers greater comfort by outperforming all others under most conditions. **SUPER THERM** is the ultimate insulation material.



LETTERS of RECOMMENDATIONS



"It is quite obvious that the paint is doing a great job in reducing the transfer of the sun's radiant heat." "The statistics obtained by our tests should be the proof needed to persuade those of lesser faith"

Frank Hofstatter, Industrial Engineer
Sacramento Army Depot

"The metal surfaces went from 130 degrees to 90 degrees. We are stopping the heat at the source, not trying to exhaust an attic full of hot air."

Roger Kuntz
AG Enterprises.



"We've decided to use SUPER THERM exclusively in our Model Block Programs". "We're painting an additional 9 houses with Super Therm this year."

Walter Wright
President Chesney Park N.I.A.
Topeka, KS.



"This year we are going on our 4th year using Super Therm as a top coat for our urethane roofs." "We have not had any trouble with either product. In my opinion, these are the best coatings on the market."

Jack Ayers
Rainbow roofing Systems
Dodge City, KS

"The reduction in temperature due to Super Therm has eliminated produce losses which of course was my prime concern, the added fuel savings being a bonus."

Bob Fountain Transport
Brisbane, Australia

"Travelodge had our pool deck resurfaced with Super Therm coating." "If we were to be asked what my most positive experience with this product was, I would have to say that it would be the cool comfort to bare feet."

Bethany Willet, General Manager
Travelodge Lawrence, KS

POLYSTYRENE FOAM

CERAMIC PAINTS

CELLULOSE FILLERS

FIBERGLASS

SUPER THERM

*RE20 two 10 mil coats (Interior App.)	✓	10"	8"	5.5"
**RE19 one 10 mil coat (Exterior)	✓	✗	✗	✗
68% Sound Blockage	✓	✓	✓	✓
MultiCeramics© Technology	✓	✗	✗	✗
One of Energy Star Best overall	✓	✗	✗	✗
California Cool Roof Program	✓	—	—	—
NASA Tested	✓	—	—	—
Works on Interior/Exterior	✓	—	—	—
Class "A" Rated "0" Flame Spread	✓	✗	✗	✗
Passed 2000 hrs Salt spray	✓	✗	✗	✗
USDA Approved	✓	—	—	—
Moisture resistant	✓	✗	✗	✗
Blocks 99.5% of Infrared	✓	—	—	—
Resists Mold & Mildew	✓	✗	✗	✗
K Factor (less is better)	0.10	0.29	0.31	0.28
25 Years residential life expectancy	✓	—	—	—
International Codes Council Approved	✓	✓	✓	✓
GSA - Listed US Government	✓	✓	✓	✓

✓ = Approved
 — = Partial approval
 ✗ = Not Possible

*RE20 Equivalency (Interior Application) supported by ASTM C236 Guarded Hot Box Test with two coats at 10 dry mils / 250 microns each.
 **RE19 Equivalency (Exterior Application) supported by ASTM C-236 Guarded Hot Box Test, ASTM E-1461-92 Thermal Diffusivity & ASTM E-1269 Specific Heat tests, additional RE9 Equivalency comes from "reflectivity" factor of SUPER THERM (92% of sunlight and 99.5% of Infrared radiation).

SUPER THERM APPLICATION



TINT TO LIGHT COLORS ONLY
Use high quality Water Base Dye at a 150% Ratio.

Applied Rate	All kinds: 100 sq.ft./gal. / 2.5 sqm. litre
Film Thickness	
Wet	All kinds: 16 mils / 400 microns
Dry	All kinds: 9-10 mils / 225-250 microns
Recommended Application Temperatures	Over 50F /10C degrees - Best -72F / 22C Not over 194F / 90C degrees
Application Required	10 mils, two coats if the surface is to be overcoated with another dark coating
Dry Times	1 hr to touch @ 22C. deg. 2 hrs to recoat
Curing Times	14-21 days
Remarks	More dry time required if in very damp climate. Be sure to remove all filters from spray equipment to prevent sifting of ceramic particles. Apply with side-to-side, up-and-down strokes for even coverage.

Outperformed fiberglass by 40% on ASTM C236 test.

K value of 0.10 results from ASTM 1269 / 1461-92

At 20 mils Outperforms 10 inches of fiberglass insulation.

SUPER THERM has 92% Sunshine Reflective Ratio.

SUPER THERM can reduce sound by 68%.

NASA "Class A" fire "0" smoke and flame spread.

Passed 2000 hour salt spray.

USDA approved and nontoxic.

UV weathering test. (UV stable).

I.C.C. approved for interior and exterior insulation.

Wal-mart rated SUPER THERM #1.

DNV approval for IMO use on all world wide vessels.

Blocks 99.5 of infrared heat radiation as per JIS A 5759 test.

IMO - International Marine Organization.

Coast Guard Approved.

Energy Star rated SUPER THERM one of the best overall.

SUPER THERM saves Sony Corporation 80% of energy usage in 3 level building every year.

Your SUPERIOR PRODUCTS REPRESENTATIVE

SUPER THERM PASSED

ASTM G 53 - ASTM E 96 - ASTM D 522 - ASTM D 412
 ASTM D1653 - ASTM E 84-89 - ASTM E 119 - ASTM C 177
 ASTM C 411 - ASTM E 1269 - ASTM E 1461-92-
 ASTM E1269 - ASTM D 1654 - ASTM D 3274 - ASTM D 4060
 ASTM E 903-96 - ASTM 1918 - ASTM C 236
 BOCA Sections - 723.2 - 723.2 - 803.2
 IMC Section 604.3
 NASA NHB 8060.1B/C Test 1 - NHB 8060.1C Test 7
 ENERGY STAR Program - JIS 5759 - USDA - CCTT

SUPER THERM K value (0.101) expressed in Lambda.

Lambda	K X 0.144 W/mK
Lambda	0.101 X 0.144
Lambda	0.015 W/mK

Based upon 0.0149" thickness.

European Lambda statistics on materials as tested for 1" (2.5cm) minimum thickness:.

Polyurethane Foam	0.028 W/mK	per 2.5cm
Polystyrene board	0.035 W/mK	"
Polystyrene expanded	0.040 W/mK	"
Mineral Wool/ Fiberglass	0.040 W/mK	"
Perlite	0.055 W/mK	"
SUPER THERM	0.015 W/mK	per 0.025 cm

LESS IS BETTER



65% SOLIDS
 VOC 67Grams/Liter
 pH: 8.5 - 9.0

OTHER AVAILABLE PRODUCTS

SP2001F	Three hours FIRE Proofing
HOT PIPE	Extreme Heat Insulation
SUPER THERM	R19 Insulation
EPOXOTHERM	Under Water Insulation
RUSTGRIP	Bio Hazard Encapsulator
ENAMO GRIP	Anti Graffiti Coating
MOIST METAL GRIP	Under Water Encapsulator
TOTAL SEAL	Potable Water Concrete Sealant
NON SKID	Non Skid Surface Coating
INNER SEAL	Water & Chemical Concrete Sealant
LINING-KOTE 6000	Chemical Concrete Liner
SUPERBASE HS	Elastomeric Primer/Sealer
SUNSHIELD 2000	Reflective Ceramic Coating
ULTRACIDE	Water Base Insecticide
ULTRASECT	Water Base Insecticide