

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

1.1 Product commercial name: EnduRoof

Product code: 50-2

1.2 Uses:

One component waterproofing and protection elastomeric material, based on polyurethane resin for the building industry.

1.3 Company/undertaking identification:

Superior Coatings & Concrete Trading
Swaefkenstraat 8
7415 EC Deventer
The Netherlands
Tel: +31 (0) 570-672971
Fax: +31 (0) 570-670343

1.4 Telephone number for emergency:

Tel.: +31 (0) 570-672971

2. HAZARDS IDENTIFICATION

2.1 Human health hazards:

Irritant by inhalation, in contact with eyes and if swallowed

2.2 Safety hazards:

No specific hazards because the product is fully polymerized by atmospheric humidity to a solid rubber like material. The product is flammable, so keep away from sources of ignition. No smoking.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Description: Polyurethane polymer.

Dangerous substance	CAS-no.	EC.no	Content	Classification
Organic solvent: Mixed xylene (o,p,m-xylene)	1330-20-7	215-535-7	3-10%	R10; Rn – R20/21 – Xi; R38

EnduRoof

According to Regulation (EU) No. 1907/2006

Specific Concentration Limit(s) of Mixed xylenes

Concentration	Classification
C ≥ 20 %	Xn; R20/21-38
12,5 % ≤ C < 20 %	Xn; R20/21

4. FIRST - AID MEASURES**4.1 First Aid - Inhalation:**

Remove to fresh air.

4.2 First Aid - Skin:

Wash immediately with alcohol, soap and water. If rapid removal does not occur, remove it after it's fully polymerized.

4.3 First Aid - Eye:

Wash immediately with soap and water. Obtain medical advice if there are persistent symptoms.

4.3 First Aid - Ingestion:

Do not induce vomiting. Give nothing by mouth. Obtain medical attention.

4.4 Advice to physicians:

Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

5. FIRE FIGHTING MEASURES**5.1 Extinguishing media:**

Sand, dry extinguishing media, foam and carbon dioxide.

5.2 Unsuitable extinguishing media: -**5.3 Protective equipment:**

Firefighters, gloves and self-contained breathing apparatus..

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions:**

Wear protective clothing, gloves and mask respirator, in case of insufficient ventilation.

6.2 Environmental precautions:

No specific hazards because the product is fully polymerized by atmospheric humidity to a solid rubber like material.

6.3 Clean-up methods:

After the mixing of the material with sand and pieces of wood transfer it to a tank for suitable incineration in accordance with local regulations.

7. HANDLING & STORAGE

7.1 Handling:

Avoid contact with eye, respiratory system and skin. In case of insufficient ventilation, wear suitable respiratory equipment.

7.2 Storage:

In the original containers tightly sealed in a dry place and keep away from sources of ignition. **Keep out of the reach of children.**

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Engineering control measures:

Not required.

8.2 Occupational exposure standards:

None established.

8.3 Hand protection:

None specified requirements.

8.4 Eye protection:

None specified requirements.

8.5 Body protection:

None specified requirements.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1 Appearance:

Viscous liquid at White, Red and different other colors.

9.2 Odour:

Characteristic.

9.3 pH:

-

9.4 Boiling point (b.p.):

-

9.5 Melting point (m.p.):

-

9.6 Flash point (F.P.):

42 °C (ASTM D93, Closed cup).

9.7 Cloud point (cp 1%w/w):

-

EnduRoof

According to Regulation (EU) No. 1907/2006

9.8 *Relative density (H₂O=1):*
1.3 - 1.4, at 20 °C (DIN 53217).

9.9 *Solubility in water:*
Immiscible.

9.10 *Soluble in:*
Organic solvents.

9.11 *Viscosity (Brookfield):*
4500-7500 cP, at 25 °C (ASTM D2196/86).

9.12 *Direction of ionization:*
-

9.13 *Active solids content percent:*
Min 90% w/w

10. STABILITY/REACTIVITY

10.1 *Stability:*
Minimum self-life in sealed containers 12 months under ambient conditions.

10.2 *Conditions to avoid:*
Humidity, long term studies at the sun and high temperature (>40 °C).

10.3 *Materials to avoid:*
Amines, alcohols and water.

10.4 *Hazardous decomposition products:*
None expected

11. TOXICOLOGICAL INFORMATION

11.1 *Eye irritation:*
May cause serious damage.

11.2 *Skin irritation:*
Irritant.

11.3 *Respiratory irritation:*
Long term inhalation studies on the product may lead to bronchoconstriction (asthmatic signs and symptoms)

11.4 *Ingestion irritation:*
Serious damage at very high concentrations. Do not delay. Go immediately to hospital.

11.5 *Information on the exposure (experimental data):*
Oral mouse: LD:50: > 2200 mg/kg

12. ECOLOGICAL INFORMATION**12.1 Mobility:**

None expected because of the fully polymerization of the product to a solid rubber like material.

12.2 Bio-accumulation:

It is like the rubbers.

12.3 Persistence/degradability:

-

12.4 Eco-toxicity:

The product does not contain heavy metals or other harmful ingredients. The contained solvents are bio-accumulate and the fillers are physical materials. The contained free isocyanates are fully polymerized by atmospheric humidity to a solid rubber like material, which is familiar to the environment.

13. DISPOSAL CONSIDERATIONS

13.1 Must be disposed of by special means, e.g. suitable incineration in accordance with local regulations.

14. TRANSPORT INFORMATION

As the product is listed as flammable may package in tightly sealed containers and keep away from sources of ignition.

UN Number: 1139

Shipping name: ROOF PAINT

Classifications:

ADR/RID	Class: 3	Packaging group: III
IMO	Class: 3.3	Packaging group: III
IATA/ICAO	Class: 3	Packaging group: III

3
1139



15. REGULATORY INFORMATION

15.1 EC Classification:

-

15.2 Contains:

-

15.3 EC Symbols:

Contains isocyanates. See the instructions of the producer

15.4 EC Risk phrases:

R10 Flammable

15.5 EC Safety phrases:

S2 Keep out of the reach of children. S23

Do not breath fumes/vapour/spray.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately of plenty of water and seek medical advice.

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

S40 To clean the floor and all objects contaminated by this material, use Solvent-01 or pure xylene.

S46 If swallowed, seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

MSDS history

16.1 Edition No:

01

16.2 First issue:

20-05-09.

16.3 Revised

According to: 2001/58/EC, 1999/45/EC, 2001/59/EC & 1907/2006/EK (L396/30.12.2006) – REACH

Disclaimer:

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the company billable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if the company has been advised of the possibility of such damages.